

Plumber's Epoxy Putty

Epoxy Putty single stick



Certified to ANSI/NSF 61

Epoxy Putty hardens like steel in 20 minutes! Ideal for plumbing, electrical, auto and home repairs. Plugs, seals, patches holes and cracks and mends almost anything broken. Can be used for underwater repairs. Excellent for fabricating or rebuilding parts and for use as an all-purpose adhesive for metals, wood, glass, masonry, ceramics and many plastics. Can be drilled, tapped, filed, sanded and painted like metal. NSF certified for use in potable water applications. **Do not use with polyethylene or polypropylene.**

Product	Harvey Stock Number	UPC Number	Case Pack	Ship Wt. Lbs.
1-1/3 oz. net wt. stick in blister card	044010	078864 440102	12	2
in plastic hanging bag on clip strip	044011	078864 440102	12	1
2 oz. net wt. stick in plastic tube in plex display with sample attached	044150-D	078864 441505	18	4
display refill	044150-12	078864 441505	12	2
display refill	044150-120	078864 441505	120	21
4 oz. net wt. stick in plastic tube in cardboard display box	044210	078864 442106	12	4



Plumber's Putty

Plumber's Putty professional grade

Plumber's Putty is easy to use and long lasting. Remains flexible and will not harden, shrink, crack or crumble even if cup is left open. Will not support bacteria. Putty is professional grade and is widely used for setting bowls, rims, strainers, faucets, etc. Meets Federal Specification TT-P-1536A. **Do not use on marble, synthetic marble, other porous surfaces or on plastic lavatories and fixtures. For these applications we recommend Harvey's Siliconized Tub Seal Latex or 100% RTV Silicone.**

7 oz. net wt. in plastic cup	043005	078864 430059	24	13
14 oz. net wt. in plastic cup in corrugated display pack	043010 043010-D	078864 430103	24 30	26 32
48 oz. (3 lb.) net wt. in plastic cup	043050	078864 430509	6	23
80 oz. (5 lb.) net wt. in plastic cup in corrugated display pack	043105 043105-D	078864 431056	6 6	35 35
15 lb. net wt. in plastic pail with handle	043155	078864 431551	4	58
§ 54 in. strip in blister card	043280	078864 432800	6	2



Siliconized Sealants and Caulk

Siliconized Tub Seal Latex

35 year guarantee, available in clear, bone, white or biscuit

Siliconized Tub Seal Latex is a water based acrylic caulk with silicone for added adhesion and low temperature flexibility. Formulated to last up to 35 years. Provides a weather resistant seal against air, moisture, dirt, dust and insects. Use indoors or out. Easy application; soap and water cleanup. Fast drying. Nonflammable. Provides excellent adhesion to brick, ceramic, vinyl, wood, glass, china, plaster, drywall and metal. Caulks around tubs, showers, enclosures, sinks, tile, walls, door moldings and windows. Also resets loose tiles. Fills joints up to 3/8" wide x 3/8" deep. Tack free in 30 minutes; paintable in 2 hours with latex or oil based paints.

clear goes on white; dries clear 5.5 fl. oz. plastic tube	032005	078864 320053	12	5
bone matches most bone/almond fixtures 5.5 fl. oz. plastic tube	032106	078864 321067	12	7
white dries to brilliant white 5.5 fl. oz. plastic tube	032010	078864 320107	12	8
10.3 fl. oz. cartridge	031050	078864 310504	12	15
biscuit 5.5 fl. oz. plastic tube	032150	078864 32150 0	12	7



Boldface UPC number indicates UPC symbol printed on package. § indicates Spanish/English packaging.

100% RTV Silicone Rubber Sealants

available in clear, white or aluminum

100% RTV Silicone Rubber Sealant creates a flexible, durable weather resistant seal between similar and dissimilar materials; provides excellent adhesion to tile, glass, porcelain, ceramic, fiberglass, non-oily woods, plaster, painted surfaces, metal, many plastics, rubber and other common building materials. It will withstand temperature extremes from -60°F. to +450°F. and is waterproof for indoor/outdoor use. Dries to the touch in one hour, cures and bonds in 24 hours. Meets Federal Specifications for use in establishments operating under Federal Meat and Poultry Inspection Program. When cured and washed ingredients remaining or which could migrate to food are listed on FDA Regulation No. 21 CFR 177.2600. Federal Specification TT-S-001543A, TT-S-00230C and ASTM-920-86. **Do not top-coat; paint will not adhere to silicone.**

Product	Harvey Stock Number	UPC Number	Case Pack	Ship Wt. Lbs.
clear sealant in 2.8 fl. oz. tube in blister card	031305	078864 313055	12	3
in 10.3 fl. oz. cartridge	031310	078864 313109	12	10
white sealant in 2.8 fl. oz. tube in blister card	031345	078864 313451	12	3
in 10.3 fl. oz. cartridge	031350	078864 313505	12	10
aluminum sealant in 10.3 fl. oz. cartridge	031320	787930 310033	12	10

Siliconized Acrylic Caulk

35 year guarantee; exceptional all-purpose caulk for indoor/outdoor use

Siliconized Acrylic Caulk is a water based acrylic caulk with silicone for added adhesion and low temperature flexibility. Provides excellent adhesion to brick, ceramic, vinyl, aluminum, painted surfaces, plaster, drywall, concrete, wood, glass, china and metal. Caulk around windows, baseboards, siding and trim, pipes, chimney flashings, air conditioners, ceiling and wall joints, door frames, moldings, corner joints, vents/ducts, masonry, tubs and sinks. Fills joints up to 3/8" wide x 3/8" deep. Tack free in 30 minutes; paintable in two hours with latex or oil-based paints.

white is mildew resistant in 10.3 fl. oz. cartridge	036010	078864 360103	12	15
clear goes on white; dries clear in 10.3 fl. oz. cartridge	036015	078864 360158	12	15
bone matches most bone/almond fixtures in 10.3 fl. oz. cartridge	036020	078864 360202	12	15

All-in-One Adhesive and Grout

superior adhesive strength

All-in-One Adhesive and Grout is a unique acrylic-based product that makes repairing and replacing cracked or loose tiles and grout easy. Completely waterproof when cured.

white in 3.75 fl. oz. plastic tube	031700	078864 317008	12	5
--	--------	----------------------	----	---

Caulking Guns

economy caulking gun steel ratchet type, with heavy spot welds	040010	078864 400106	12	12
deluxe caulking gun zinc-plated, with tip-cutter and seal punch	040025	078864 400250	12	14

Boldface UPC number indicates UPC symbol printed on package. § indicates Spanish/English packaging.



Specialty Sealants

Plastic Lead

easy to use—just add water

Plastic Lead joins plastic to other materials, patches cement and drywall and is an excellent lead substitute for caulking, plumbing, patchwork and hobby applications.

Product	Harvey Stock Number	UPC Number	Case Pack	Ship Wt. Lbs.
§ 8 oz. net wt. in plastic jar	047150	078864 471502	6	5

Furnace Cement

high temperature, ready to use, no mixing

Furnace Cement withstands the same temperatures as fire brick for use on coal or wood burning furnaces and stoves. Repairs casting cracks; fills voids in and around furnace and stove parts. Excellent firebrick mortar repair. Furnace can be used immediately. Withstands temperatures up to 3000°F. and dries to a hard **gray** finish.

10.3 fl. oz. in cartridge	045005	078864 450057	12	19
8 fl. oz. (1/2 pint) in plastic cup	045020	078864 450200	12	14
16 fl. oz. (1 pint) in plastic cup	045050	078864 450507	6	14
32 fl. oz. (1 quart) in plastic cup	045105	078864 451054	6	27
1 gallon in plastic pail with handle	045155	078864 451559	4	69

Soil Seal

ready to use, no heating or mixing

Soil Seal is a plastic lead substitute for caulking soil pipe joints. Repairs enamelware, china, cast iron and clay soil pipe. Will not shrink, shrivel or crack and is impervious to water, steam, oil and gasoline. Putty-like in consistency, can be molded with hands or applied with a putty knife or similar tool. Skins over in minutes. **Wear rubber gloves to prevent contact with skin.**

8 fl. oz. (1/2 pint) in metal can	047010	078864 470109	12	12
16 fl. oz. (1 pint) in metal can	047060	078864 470604	12	23

Roof Seal

wet/dry black plastic flashing

Roof Seal is a flashing and roof compound for wet or dry application. A highly flexible cement specially formulated with asphalt and selected additives to provide adhesion to wet surfaces and is recommended for installation and repair of flashing and roofs. Roof Seal is a filler and sealer for patching cracks and breaks in roofing surfaces, firewalls, chimneys, gutters, flashings and roof mounted heating and cooling units. Roof Seal offers outstanding resistance to water. It can be used to stop leaks around vent pipes, spouts, flashing and gutters and is suitable for sealing metal building seams and foundations. This special formulation of highly refined asphalt remains soft and pliable for years. Meets Federal Specification SS-C-00153a Type 1.

32 fl. oz. (1 quart) in metal can	049010	078864 490107	12	23
1 gallon in metal can with handle	049060	078864 490602	6	50
5 gallons in pail	049115	078864 491159	1	46

Neoprene Roof Sealant

professional grade, 20 year guarantee

Neoprene Roof Sealant is a unique professional grade elastomeric flashing and repair product that cures to a long-lasting rubber membrane 50 times stronger than plastic cements. This product remains flexible through extreme temperature ranges. It has a 20 year guarantee that matches any roofing system warranty it is used with. Its non-sag properties and its exceptional adhesion guarantee that it is the perfect cement for the construction and repair of all flashings, parapet walls, copings and chimneys. This product is ideally suited for sealing cracks, holes and tears in built-up roofs (asphalt and tar) and modified bitumen single plys. It may also be used to repair EPDM rubber sheets.

10.3 fl. oz. in cartridge	049125	027134 101069	12	12
---------------------------	--------	----------------------	----	----



Boldface UPC number indicates UPC symbol printed on package. § indicates Spanish/English packaging.

